

# QUICK REFERENCE MAINTENANCE COATING CHART



SURFACES

PREP METHOD

PRIMERS

FINISHES

FS 974 Zinc Chromate Metal Primer (yellow)

Anti-Rust Industrial Maintenance Enamel

FS 2590 Fast Dry Metal Primer (gray)

FS 977 Soy Zinc Primer (gray)

Exterior Oil Primer 588

Exterior Latex Primer 488

FS 977 Soy Zinc Primer/Finish

FS 1500 Self Priming Tank Enamel (white)

Anti-Rust Industrial Maintenance Enamel

FS 969 Polyurethane Gloss Enamel

FS 3100 Exterior Latex Metal Building Paint (white)

Select the Right Product for the Right Surface and the Right Job

**Anti-Rust Industrial Maintenance Enamel**  
For interior & exterior uses. Resistant to moisture, chemicals and abrasion with deep penetrating adhesion.  
GL #72216 - 21952 Primer White  
GL #114901 - 21951 Primer Red Oxide  
GL #72043 - 21900 White  
PL #139547 - 21900 White  
GL #130409 - 21934 Gray  
QT #129484 - 23703 Primer Galvanized  
GL #139660 - 23703 Primer Galvanized

**Guardian Pro Exterior 588 Oil & 488 Latex Primer**  
Seals exterior bare woods for proper topcoat holdout. May be topcoated with oil or latex.  
GL #72059 - 488 Latex  
PL #72060 - 488 Latex  
GL #72002 - 588 Oil  
PL #72003 - 588 Oil

**Medallion 4260 Series Semi-Gloss Direct To Metal**  
Latex finish for exterior surfaces. Comes in 6 factory colors. Protects against rust.  
GL #175727 Bright White  
PL #200465 Bright White  
GL #175728 Classic Green  
GL #175729 Classic Red  
PL #200466 Classic Red  
GL #175730 Classic Brown  
GL #200967 4264 Light Stone  
GL #200968 Ash Gray



**FS White 3100 Satin Exterior Latex Building Paint**

High quality latex finish for exterior and interior surfaces. Extremely durable and resistant to yellowing.  
GL #200966 White  
PL #189882 White  
Exterior Latex Tint Bases  
GL #200597 - 4102 med base  
PL #189884 - 4102 med base  
GL #200598 - 4105 clear base  
PL #189885 - 4105 clear base

SURFACES	PREP METHOD	FS 974 Zinc Chromate Metal Primer (yellow)	Anti-Rust Industrial Maintenance Enamel	FS 2590 Fast Dry Metal Primer (gray)	FS 977 Soy Zinc Primer (gray)	Exterior Oil Primer 588	Exterior Latex Primer 488	FS 977 Soy Zinc Primer/Finish	FS 1500 Self Priming Tank Enamel (white)	Anti-Rust Industrial Maintenance Enamel	FS 969 Polyurethane Gloss Enamel	FS 3100 Exterior Latex Metal Building Paint (white)	Medallion 4260 Series DTM-6 pre-tinted colors	FS 998 Ready Mix Aluminum
<b>BUILDINGS</b>														
WOOD	1,4,5,7					BEST - 588						BEST	GOOD	
MASONRY	1,4,5											GOOD		
HARDBOARD	1,4,5											BEST		
METAL	1,4,5,7		GOOD		BEST				GOOD			BEST	BEST	
GALVANIZED METAL	1,4,5		GOOD - 23703		BEST	GOOD - 488	BEST		GOOD			BEST		BEST
FERROUS METAL TRIM/PIPING	1,4,5	BEST	GOOD - 21952	BEST	BEST		GOOD			BEST		GOOD		BEST
FACTORY FINISHED SIDINGS	1,4,5											BEST	BEST	
<b>FERTILIZER HANDLING EQUIPMENT</b>														
OUTSIDE DRY FERTILIZER EQUIPMENT	3,4,7	GOOD		BEST							GOOD			
INSIDE DRY FERTILIZER EQUIPMENT	3,4,7	GOOD		BEST							GOOD			
LIQUID FERTILIZER/ANHYDROUS EQUIPMENT	3,4,7	GOOD		BEST				GOOD		GOOD				
LIQUID FERTILIZER/ANHYDROUS EQUIPMENT	3,4,7	GOOD		BEST				GOOD		GOOD				
PETROLEUM/LIQUID PROPANE	3,4,7	BEST		BEST				BEST		BEST				
PIPES, PUMPS, DOCKS, ETC.	4,5,7	BEST		BEST				GOOD		BEST			GOOD	
L.P. CYLINDERS	4,5,7	BEST		BEST				GOOD		GOOD			BEST	
FERROUS METAL	1,4			BEST										
SANDED ALUMINUM	1,4			BEST										
SANDED FIBERGLASS	3,4,7			BEST										

PREPARATION METHODS  
 1. Solvent Cleaning    2. Chemical Stripping    3. Blast Cleaning    4. Power Tool Cleaning    5. Hand Tool Cleaning    6. Pre-Treatment/Painting    7. Pre-Treatment/Priming    8. Mildew Removal    9. Concrete Etching    Refer to Paint Reference Guide for specific and/or detailed information



**FS 974 Yellow Zinc Chromate Metal Primer**  
A superior rust inhibiting primer for bare ferrous metal such as iron and steel. Provides excellent adhesion under oil or latex finish coats. (Do not topcoat with epoxy or acrylic urethane).  
GL #72075



**FS 2590 Gray Fast Dry Metal Primer**  
A fast drying, rust inhibiting, gray metal primer formulated for use over properly prepared ferrous metal surfaces. Also provides excellent adhesion as a prime coat on fiberglass surfaces. Fast dry allows for top coating after 1 hour.  
GL #72465



**FS 998 Ready Mix Aluminum**  
For use on exterior metal or wood surfaces. Bright, heat reflective heavy-duty aluminum paint.  
GL #72104  
PL #72105



**FS 969 White Polyurethane Gloss Enamel**  
Excellent gloss retention, gas, oil and grease resistance. Recommended for areas where occasional splashes and spills may occur.  
GL #72083  
PL #72084



**FS 1500 White Self Priming Tank Enamel**  
Easy to use, rust inhibiting product which protects metal against mold and fungi growth.  
GL #72458  
PL #72459



**FS 977 Soy Zinc Primer/Finish**  
Provides excellent bonding and surface rust resistance. For use as primer coat or finish coat of ferrous metal or galvanized metal. Zinc coating reconditions deteriorated galvanized metal extending its life and effectiveness.  
GL #72101